

IN THE SPECIFICATION

Please change the specification as follows:

Page 2, second full paragraph:

In order to solve the above-discussed problems, according to the present invention, the gas-insulated switchgear, in which a main circuit components are accommodated within a tank hermetically filled with an electrically insulating gas, comprises at least one switchgear module in which a disconnecter with a grounding switch and an electrically insulating frame ~~capable of~~ for selectively supporting an interrupter including a ~~vacuum-valve~~ vacuum switch tube are disposed in the tank in a vertically stacked relationship, and in which the disconnecter and the ~~vacuum-valve~~ vacuum switch tube are connected ~~between their movable rods, specifically, the~~ disconnecter and a movable rod of said vacuum switch tube are electronically connected to each other.

Paragraph bridging pages 5 and 6,

As has been apparent from the foregoing description, according to the present invention, the gas-insulated switchgear in which main circuit components are accommodated within a tank hermetically filled with an electrically insulating gas comprises at least one switchgear module in which a disconnecter with a grounding switch and an electrically insulating frame ~~capable of~~ for selectively supporting an interrupter including a ~~vacuum-valve~~ vacuum switch tube are disposed in the tank in a vertically stacked relationship, and in which said disconnecter and said ~~vacuum~~ valve vacuum switch tube are connected ~~between their movable rods, specifically, the~~ disconnecter and a movable rod of said vacuum switch tube are electronically connected to each other. Therefore, a gas-insulated switchgear can be obtained in which the module tanks are the same to each other in dimensions and configuration, and that can be adapted to various electric equipments to be accommodated within the module.